

ELASTOMARK 818

(former AKRYLOEPOX DILUTED IN WATER)

ACRYLIC-BASED PAINT FOR FLOORINGS FOR INTERNAL AND EXTERNAL SURFACES

GENERAL CHARACTERISTICS

ELASTOMARK 818 is acrylic-based paint for floorings, for internal and external surfaces.

- It can be applied quickly and easily, having low cost.
- Provides strong adhesion to the substrate and resistance to weather conditions.
- Suitable for painting athletic courts, cement floorings, mosaics and asphalt surfaces, as well as lining at athletic courts.
- Eliminates dust from decay in old & new floorings
- Ideal for athletic courts, schools, hotels, parking areas, pavements, hallways etc.

TECHNICAL DATA

Basis:	one-component acrylic resin
Appearance:	viscous liquid
Colors:	white, indian red, green, grey, blue, ochre and on request from RAL color card for orders more than 300kg
Viscosity:	19.500 ± 500 mPa•s at 23°C
Density:	1,539 ± 0,047 gr/cm ³
pH:	7,60 ± 0,1
Temperature for the application and drying of the material:	5 - 30°C after 24 hours in 25 °C
Walkability:	

PREPARATION - APPLICATION

Applied only on dry surfaces, protected from arising humidity and free of materials that might prevent bonding e.g. dust, loose particles, grease etc. The success in the application depends on the right preparation of the underlay and use of the material.

- **Good, dry** cleaning of the surface from dust and residues with vacuum cleaner and squeegees.
- Priming of the surface with joining resin **RITIVEX (1102)** for the proper adhesion of the sub-floor. Application of one or more layers until the surface is saturated. Avoid the creation of puddles of the material. Consumption: 150-250gr/m², depending on the absorption of the underlay.
- When the primer begins to dry (approximately 1 hour depending on the ambient temperature), follows the application of **AKRYLOEPOX (818)**.
- Depending on the ambient temperature **AKRYLOEPOX (818)** can be diluted with 15% water, prior to application, in order to achieve better fluidity. It is applied in two or more layers. The next layer follows as soon as the previous starts to dry.

CONSUMPTION

400 - 500 gr/m² in two layers, depending on the absorbency and roughness of the

Thessaloniki Office

10, 25th Martiou str., N. Efkarpia,
P.C.: 56429, Thessaloniki Greece
T.: (+30) 2310 680105, (+30) 2310 680382
F.: (+30) 2310 692866

e-mail: exports@polat.gr

Athens Office

109, Vouliagmenis Avenue, Glifada,
P.C.: 16674, Athens Greece
T.: (+30) 210 9647320
F.: (+30) 210 9646317

www.polat.gr



underlay.

APPLICATION

TOOLS Nappy rolls, brushes, spray. Tools should be cleaned with **WATER** immediately after use.

PACKAGING

Supplied in drums of 10kg and 25 kg.

STORAGE

One year in unopened containers in dry places with minimum temperature 5°C.

CAUTION

The application must take place in well-aired places using protective gloves. Skin or eye contact must be avoided, otherwise wash carefully with soap and water.

For more information consult the material safety data sheet.

The information given here is true, represents our best knowledge and is based not only on laboratory work, but also on field experience. However, because of numerous factors affecting results we offer this information without any guarantee and no patent liability is assumed. For additional information or questions, contact the technical department of POLAT S.A.

Thessaloniki Office

10, 25th Martiou str., N. Efkarpia,
P.C.: 56429, Thessaloniki Greece
T.: (+30) 2310 680105, (+30) 2310 680382
F.: (+30) 2310 692866

e-mail: exports@polat.gr

Athens Office

109, Vouliagmenis Avenue, Glifada,
P.C.: 16674, Athens Greece
T.: (+30) 210 9647320
F.: (+30) 210 9646317

www.polat.gr

